

1. Identification

Product identifier	Slow Dry Thinner		
Other means of identification			
Product Code	PC402		
Recommended use	Lacquer thinner		
Manufacturer/Importer/Supplier/Distributor information			
Manufacturer			
Company name	Performance Products		
Address	6424 3rd Line Road LaPorte IN 46350 United States		
Telephone	General Assistance	866-228-6528	
E-mail	www.performanceplusproduct.com		
Contact person	Andy Squires		
Emergency phone number	Emergency Contact	800-424-9300	

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, oral	Category 3
	Acute toxicity, dermal	Category 4
	Acute toxicity, inhalation	Category 3
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1B
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, single exposure	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	

Label elements**Signal word**

Danger

Hazard statement

Highly flammable liquid and vapor. Toxic if swallowed. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. Toxic if inhaled. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging the unborn child. May cause damage to organs. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor. Rinse mouth. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

22% of the mixture consists of component(s) of unknown acute dermal toxicity. 65% of the mixture consists of component(s) of unknown acute inhalation toxicity. 26% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 26% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Xylene	1330-20-7	0<40
Methyl Acetate	79-20-9	0<30
Methanol	67-56-1	0<30
Acetone	67-64-1	0<10
MEK	78-93-3	0<10

Other components below reportable levels

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Carbon dioxide (CO₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe the mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency

Ingredient	CAS	OSHA TWA	OSHA STEL	ACGIH TWA	ACGIH STEL
Methanol	67-56-1			(200 ppm)/2008	(250 ppm)/2008
Methyl Acetate	79-20-9			(200 ppm)/2010	(250 ppm)/2010
Acetone	67-64-1			(200 ppm)/2010	(500 ppm)/2010
MEK	78-93-3		(300 ppm)/2008	(200 ppm)/2008	
Xylene	1330-20-7	100 ppm	150PPM (655 mg/m3)	(100 ppm)/2008	(100 ppm)/2008

Appropriate engineering controls

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	Not available.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point -138.82 °F (-94.9 °C) estimated

Initial boiling point and boiling range 132.89 °F (56.05 °C) estimated

Flash point -4.0 °F (-20.0 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 1.1 % estimated

Flammability limit - upper (%) 12.8 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 66.85 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 550 °F (287.78 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 7.17 lbs/gal

Flammability class Flammable IB estimated

Percent volatile 68.23 %

Specific gravity 0.86

VOC 4.89 lbs/gal Material

585.91 g/l Material

835.38 g/l Regulatory

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents.

Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Toxic if inhaled. May cause damage to organs by inhalation. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Harmful in contact with skin. Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Toxic if swallowed.

Physical, Chemical and Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation.

Toxicological characteristics Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Toxic if inhaled. Toxic if swallowed. Harmful in contact with skin. Narcotic effects.

Components	Species	Test Results
<u>acetone (CAS 67-64-1)</u>		
Acute		
Dermal		
LD50	Rabbit	20000 mg/kg 20 ml/kg
Inhalation		
LC50	Rat	76 mg/l, 4 Hours 50.1 mg/l, 8 Hours
Oral		
LD50	Mouse Rabbit Rat	3000 mg/kg 5340 mg/kg 5800 mg/kg
<u>methanol (CAS 67-56-1)</u>		
Acute		
Dermal		
LD50	Rabbit	15800 mg/kg
Inhalation		
LC50	Rat	64000 ppm, 4 Hours 87.5 mg/l, 6 Hours
Oral		
LD50	Monkey Mouse Rabbit Rat	2 g/kg 7300 mg/kg 14.4 g/kg 5628 mg/kg
<u>Xylene (1330-20-7)</u>		
Acute		
Dermal		
LD50	Rabbit	4,350 mg/kg

Components	Species	Test Results
Inhalation LC50	Rat	6,350 ppm, 4 Hours
Oral LD50	Rat	4,350 mg/kg
<u>methyl ethyl keytone (CAS 79-93-3)</u>		
Acute Dermal LD50	Rabbit	6,480 mg/kg
Inhalation LC50	Rat	23.5 mg/l, 8 Hours
Oral LD50	Rat	2,737 mg/kg
<u>methyl acetate (79-20-9)</u>		
Acute Dermal LD50	Rabbit	2,000 mg/kg
Inhalation LC50	Rat	49 mg/l
Oral LD50	Rat	6,482 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage
eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Suspected of damaging the unborn child.

Specific target organ toxicity – Single exposure May cause damage to organs. May cause drowsiness and dizziness

Specific target organ toxicity – Repeated exposure Causes damage to organs through prolonged or repeated exposure

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
acetone (CAS 67-64-1)		
Aquatic		
Crustacea	EC50 Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
methanol (CAS 67-56-1)		
Aquatic		
Crustacea	EC50 Water flea (Daphnia magna)	10000 mg/l, 48 hours
Fish	LC50 Fathead minnow (Pimephales promelas)	100 mg/l, 96 hours
xylene (CAS 1330-20-7)		
Aquatic		
Crustacea	EC50 Water flea (Daphnia magna)	1.81 – 2.38 mg/l, 48 hours
Fish	LC50 Pimephales promelas (fathead minnow)	26.7 mg/l, 96 hours
methyl ethyl keytone (CAS 79-93-3)		
Aquatic		
Fish	EC50 Pimephales promelas	3,220 mg/l, 96 Hours
methyl acetate (CAS 79-20-9)		
Aquatic		
Fish	LC50 Fathead Minnow	320 - 399 mg/l, 96 Hours
Persistence and degradability	No data is available on the degradability of this product.	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1263
UN proper shipping name	Paint, Paint Related Material
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB2, T7, TP1, TP8, TP28
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242

IATA

UN number	UN1263
UN proper shipping name	Paint, Paint Related Material
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
ERG Code	3H
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG


UN number	UN1263
UN proper shipping name	Paint, Paint Related Material
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	2
Environmental hazards	
Marine pollutant	Yes
EmS	F-E, <u>S</u> - <u>E</u>
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.



DOT



IATA; IMDG



Marine Pollutant

General information

DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)	Listed.
Methanol (CAS 67-56-1)	Listed.
Xylene (CAS 1330-20-7)	Listed.
Methyl acetate (CAS 79-20-9)	Listed.
Methyl ethyl ketone (CAS 78-93-3)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
xylene	1330-20-7	0<30
Methanol	67-56-1	0<30
Methyl Acetate	79-20-9	0<30
Acetone	67-64-1	0<10
Methyl ethyl ketone	78-93-3	0<10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methanol (CAS 67-56-1)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (1330-20-7)	Listed.
Methyl ethyl ketone (CAS 78-93-3)	Listed.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532.

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35%WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Methanol (CAS 67-56-1)

Xylene (CAS1330-20-7)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)

Methyl acetate (CAS 79-20-9)

Methyl ethyl keytone (CAS 78-93-3)

Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Methanol (CAS 67-56-1)

Methyl acetate (CAS 79-20-9)

Methyl ethyl keytone (CAS 78-93-3)

Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Methanol (CAS 67-56-1)

Methyl acetate (CAS 79-20-9)

Methyl ethyl keytone (CAS 78-93-3)

Xylene (CAS 1330-20-7)

US. Rhode Island RTK

Acetone (CAS 67-64-1)

Methanol (CAS 67-56-1)

Methyl acetate (CAS 79-20-9)

Methyl ethyl keytone (CAS 78-93-3)

Xylene (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

methanol (CAS 67-56-1)

Listed: March 16, 2012

Toluene (CAS 108-88-3)

Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

methanol (CAS 67-56-1)

Listed: March 16, 2012

Toluene (CAS 108-88-3)

Listed: August 2, 2009

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 04-26-2015

Version # 01

HMIS® ratings Health: 3*
Flammability: 3
Physical hazard: 0

NFPA ratings Health: 3
Flammability: 3
Instability: 0

Disclaimer The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.